



CUNX Universal Mounts

MODEL / MODELO: CUNX SPECIFICATIONS / ESPECIFICACIONES

Model			CUNX36	CUNX60
Power supply		V-Ph-Hz	220V-1Ph-60Hz	220V-1Ph-60Hz
Cooling	Capacity	Btu/h	36000	55000
	Input	W	4013	7200
	Rated Current	A	1.09	1.9
MCA		A	1.5	3.0
Operation Control			Remote Controller	Remote Controller
Indoor Coil	Number of Rows		3	3
	Tube pitch(a)x row pitch(b)	mm	21×13.37	21×13.37
	Fin Spacing	mm	1.4	1.4
	Fin Type		Hydrophilic	Hydrophilic
	Tube outside dia. and type	mm	7 / Inner Grooved	7 / Inner Grooved
Coil length x height x width		mm	948×252×40.11	1318×252×70
Indoor Noise Level		dB(A)	51-57	55
Indoor Dimensions	Unit (W×H×D)	mm	1250×235×675	1670×235×675
	Package (W×H×D)	mm	1380×325×765	1750×325×770
	Net/Gross Weight	kg	32/37	40/46
Indoor Fan Motor	Brand		Weiling	Kaibang
	Model		YSK110-180LD-4P2	YSK110-59LD-4P17
	Input	W	360	135*2
	Output	W	180	70*2
	Capacitor	uF	5	3*2
Outer Diameter of Gas Pipe		mm	φ9.52	φ9.52
Refrigerant Piping	Liquid side/ Gas side	inch	3/8 3/4	3/8 3/4
	Max. Pipe length	m	20	20
Cooling Operation Ambient Temperature Range		°C	16~32	16~32