



COOL WITH MAXIMUM EFFICIENCY

UP TO 22 SEER2

**COOLING
ONLY**



Classic
AIR CONDITIONERS

AHRI CERTIFIED™
www.ahridirectory.org



Features



Arctic Inverter Cooling Only Mini Split System

SPECIFICATIONS / ESPECIFICACIONES

Model			GWARC09SA2 / GRARC09ASA2	GWARC12SA2 / GRARC12ASA2	GWARC09S2 / GRARC09AS2	GWARC12S2 / GRARC12AS2	GWARC18S2 / GRARC18AS2	GWARC24S2 / GRARC24AS2	GWARC36S3 / GRARC36AS3
Power supply		V-Ph-Hz	115-60-1	115-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1	208/230-60-1
Cooling	Capacity	Btu/h	9100	12000	9100	12000	1800	22000	33600
	Input (Min/Max)	W	140/1050	140/1450	120/1350	140/1450	280/2150	448.1/2600	670/4000
	Rated Current	A	11.7	15.8	6.5	6.8	10.5	12	20
	SEER/SEER2	Btu/w	20/20	20/20	20.5/20.5	20/20	19.5/19.5	21/22	20/20
Max. current		A	25	25	15	15	15	25	35
Compressor	Model		FTz-AN108ACBD	FTz-AN108ACBD	QXF-A082zC170	FTz-AN108ACBD	QXF-M130zF170	QXFS-M180zX170	QXFS-D280zX070
	Type		Rotary	Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
	Input	W	857	857	756.6	857	1157	1350	2294
	Rated current (RLA)	A	11.5	14.5	4.9	5.8	5.6	12.2	16.0
	Refrigerant		R410A	R410A	R410A	R410A	R410A	R410A	R410A
Outdoor noise level		dB(A)	61	62	59	62	69	69	72
Indoor Dimensions	Unit (W×H×D)	inch	33×11×8	33×11×8	33×11×8	33×11×8	38x12x9	42x13x10	53x13x10
	Package (W×H×D)	inch	36×11×15	36×11×15	36×11×15	36×11×15	40x15x12	44x16x13	56x17x14
Outdoor Dimensions	Unit (W×H×D)	inch	29×22×13	29×22×13	29×22×13	29×22×13	38x22x15	38x26x16	39x29x17
	Package (W×H×D)	inch	31×15×24	31×15×24	31×15×24	31×15×24	37x17x24	40x18x29	42x19x31
Refrigerant piping	Length	m	7.5	7.5	7.5	7.5	7.5	7.5	7.5
	Additional Gas Charge	g/m	15	15	15	15	15	15	15
	Max Distance Height	m	12	10	12	10	10	10	10
	Max Distance Length	m	20	20	20	20	25	25	25
	Outer Diameter of Liquid Pipe	inch	φ0.2	φ0.2	φ0.2	φ0.2	φ0.2	φ0.2	φ0.2
	Outer Diameter of Gas Pipe	inch	φ0.3	φ0.3	φ0.3	φ0.3	φ0.4	φ0.6	φ0.6
Outdoor Weight	Net weight	lbs	62.8	63.9	59.5	60.6	79.3	94.7	125.6
	Gross weight	lbs	68.3	69.4	65	66.1	85.9	104.7	136.6
Cooling Operation Ambient Temperature Range		°F	0~115	0~115	0~115	0~115	0~115	-4~122	-4~115



Wi-Fi compatible



Copper & Aluminum Pipe Kits



Golden Coating Technology