

EVERYDAY

COMFORT SIMPLIFIED

Classic ❄️
AIR CONDITIONERS




Features




MODEL / MODELO: MWEIC/MREIC SPECIFICATIONS / ESPECIFICACIONES

Model		MWEIC09S/ MREIC09DS	MWEIC12S/ MREIC12DS	MWEIC18S/ MREIC18DS	MWEIC24S/ MREIC24DS
Power supply		V-Ph-Hz	220-240/1/50	220-240/1/50	220-240/1/50
Cooling	Capacity	Btu/h	9000	12000	18000
	Input	W	910	1214	1850
	Rated current	A	4.04	5.39	8.5
	EER	btu/h	9.89	9.89	9.72
Compressor	Model		KSK89D33UEZD38	KSK89D33UEZD3	KSN140D21UFZ
	Type		Rotary	Rotary	Rotary
	Brand		GMCC	GMCC	GMCC
Indoor noise level (Hi/Mi/L0)		dB(A)	38/35/27	40/35/28.5	44/39/33
Indoor unit	Dimension (W*D*H)	mm	715x194x285	805x194x285	957x213x302
	Packing (W*D*H)	mm	780x270x365	870x270x365	1035x295x385
	Net/Gross weight	Kg	7.2/9.3	7.8/10	10.5/13.4
Outdoor noise level		dB(A)	55	54.5	57
Outdoor unit	Dimension (W*D*H)	mm	720x270x495	720x270x495	765x303x555
	Packing (W*D*H)	mm	835x300x540	835x300x540	887x337x610
	Net/Gross weight	Kg	19.7/21.4	19.6/21.5	26.3/28.6
Refrigerant type		Type / kg	R410A/0.42kg	R410A/0.52kg	R410A/0.72kg
Connecting Pipe Diameter	Liquid Pipe	mm/inch	6.35/ 1/4	6.35/ 1/4	6.35/ 1/4
	Gas Pipe	mm/inch	9.52/ 3/8	9.52/ 3/8	12.7/ 1/2
Max Refrigerant Pipe Length		M	25	25	30
Room Temperature Range (Indoor)		°C	17~32	17~32	17~32
Room Temperature Range (Outdoor)		°C	0~50	0~50	-15~50

Highlights



Dual Filtration



Self Cleaning



Golden Coating Technology

DC INVERTER