



# ROUND FLOW CASSETTE

Seamless Room Cooling

# Features

360 Air Supply




Fresh Air Intake



Digital Display




3D Fan Blade



Ultra-tin Body



Water Pump



## MODEL / MODELO: CCACT SPECIFICATIONS / ESPECIFICACIONES

Model			CCACT24	CCACT36	CCACT48	CCACT60
Indoor power supply		V/Ph/Hz	208~230/1/60	208~230/1/60	208~230/1/60	208~230/1/60
Cooling	Capacity	Btu/h	24000	36000	48000	60000
		W	7032	10548	14064	17580
	Input	W	102	102	160	160
	Rated current	A	0.7	0.7	0.8	0.8
Indoor fan motor	Brand		KAIBANG	KAIBANG	KAIBANG	KAIBANG
	Model		S.TB-DQ-YDK-45Q-8P2	S.TB-DQ-YDK-45Q-8P2	S.TB-DQ-YDK-80Q-8P2	S.TB-DQ-YDK-80Q-8P2
	Capacitor	μF	2.5	2.5	4	4
	Speed(Hi/Me/Lo)	r/min	850/730/580	850/730/580	800/750/650	800/750/650
Indoor coil	Number of rows		2	2	2	2
	Tube pitch(a)xrow pitch(b)	mm	21×13.37	21×13.37	21×13.37	21×13.37
	Fin spacing	mm	1.45	1.45	1.45	1.45
	Fin type		Hydrophilic	Hydrophilic	Hydrophilic	Hydrophilic
	Tube outside dia. and type	mm	Φ7	Φ7	Φ7	Φ7
			inner grooved	inner grooved	inner grooved	inner grooved
Number of circuits		8	8	12	12	
Indoor air flow(High speed)		m3/h	1200	1200	1900	1900
Max pressure		MPa	4.0	4.0	4.5	4.5
Refrigerant type			R410A	R410A	R410A	R410A
Refrigerant piping	Liquid side/Gas side	mm	Φ9.52/Φ15.88	Φ9.52/Φ19.05	Φ9.52/Φ19.05	Φ9.52/Φ19.05
Drainage pipe		mm	25	25	25	25
Operation temp		°C	16~32	16~32	16~32	16~32
Ambient temp		°C	18~43	18~43	18~43	18~43
Application area		m2	28-50	40-70	55~95	60~105

TGM Industries, Inc. 2024