



Golden Fin

Power & Signal  
Cable IncludedInstallation Kit  
Included

# Arctic Inverter Series

## Serie de inversores Arctic

### MODEL / MODELO: GWARD\_SA2 / GRART\_ASA2

### SPECIFICATIONS / ESPECIFICACIONES

Model			GWARD09SA2 / GRART09ASA2	GWARD12SA2 / GRART12ASA2
Power supply		V-Ph-Hz	115-60-1	115-60-1
Cooling	Capacity	Btu/h	9100	12000
	Input (Min/Max)	W	140/1050	140/1450
	Rated Current	A	11.7	15.8
	<b>SEER/SEER2</b>	<b>Btu/w</b>	<b>20/20</b>	<b>20/20</b>
Max. current		A	25	25
Compressor	Model		FTz-AN108ACBD	FTz-AN108ACBD
	Type		Rotary	Rotary
	Input	W	857	857
	Rated current (RLA)	A	11.5	14.5
	Refrigerant		R410A	R410A
Outdoor noise level		dB(A)	61	62
Indoor Dimensions	Unit (W×H×D)	mm	845×289×209	845×289×209
	Package (W×H×D)	mm	921×281×379	921×281×379
Outdoor Dimensions	Unit (W×H×D)	mm	732×555×330	732×555×330
	Package (W×H×D)	mm	794×376×615	794×376×615
Refrigerant piping	Length	m	7.5	7.5
	Additional Gas Charge	g/m	15	15
	Max Distance Height	m	12	10
	Max Distance Length	m	20	20
	Outer Diameter of Liquid Pipe	mm	φ6	φ6
	Outer Diameter of Gas Pipe	mm	φ9.52	φ9.52
Outdoor Weight	Net weight	Kg	28.5	29
	Gross weight	Kg	31	31.5
Cooling Operation Ambient Temperature Range		°F	0~115	0~115