



Golden Fin

Power & Signal
Cable IncludedInstallation Kit
Included

DC INVERTER

Classic
AIR CONDITIONERS



Arctic Heat Pump Inverter Series

Serie Arctic Inverter bomba de calor

MODEL / MODELO: GWHARC36S3 / GRHARC36AS3

SPECIFICATIONS / ESPECIFICACIONES

| Model | | GWHARC36S3/GRHARC36AS3 | |
|--|------------------------------|------------------------|----------------------------------|
| Power supply | | V-Hz-Ph | 208/230 - 60 - 1 |
| Cooling | Capacity | Btu/h | 33600 |
| | Input (Min/Max) | W | 670/4000 |
| | Rated current | A | 20.00 |
| | SEER/SEER2 | Btu/w | 20/20 |
| Heating | Capacity | Btu/h | 34600 |
| | Input (Min/Max) | W | 600/3950 |
| | Rated current | A | 18 |
| | HSPF/HSPF2 | W/w | 9.00/8.5 |
| Compressor | Type | | Rotary |
| | Model | | QXFS-D280zX070 |
| | Refrigerant oil/oil charge | kg | 2.4 |
| Indoor air flow (Super strong/high/medium high/medium/medium low/low/super low) | | m ³ /h | 1550/1250/1200/1100/1000/900/800 |
| Indoor sound power (Super strong/high/medium high/medium/medium low/low/super low) | | dB(A) | 66/60/57/55/52/50/47 |
| Indoor Unit | Dimension(W*D*H) | mm | 1350×326×253 |
| | Packing (W*D*H) | mm | 1441×421×367 |
| | Gross weight | kg. | 24.5 |
| Outdoor air flow | | m ³ /h | 4500 |
| Outdoor sound power (Hi/Mi/Lo) | | dB(A) | 72 |
| Outdoor Unit | Dimension(W*D*H) | mm | 1000×746×427 |
| | Packing (W*D*H) | mm | 1080×483×810 |
| | Gross weight | kg | 63 |
| Refrigerant type | | | R410A |
| Refrigerant charge | | kg | 2.4 |
| Refrigerant piping | Length | m | 7.5 |
| | Additional Gas Charge | g/m | 50 |
| | Liquid side/ Gas side | mm | φ6 / φ16 |
| | Max. refrigerant pipe length | m | 25 |
| | Max. height | m | 10 |
| Room Temperature | Indoor (cooling/ heating) | °F | 61~86 |
| | Outdoor (cooling/heating) | °F | -4~115 / -13~75 |
| Application area (cooling standard) | | m ² | 46-70 |