




Duct Fan Coil



Fan coil de ducto

MODEL / MODELO: MHXT SPECIFICATIONS / ESPECIFICACIONES

Model			MHXT24	MHXT36	MHXT48	MHXT60
Power supply		Ph-V-Hz	220-230~1-60	220-230~1-60	220-230~1-60	220-230~1-60
Indoor fan motor	Model		YKSS-115-4-21	YKSS-115-4-21	YKSS-480-4-2	YKSS-480-4-2
	RLA	A	1.095	1.095	2.75	2.75
	Speed	r/min	1050/900/750/650	1050/900/750/650	1040/900/800	1000 / 900 / 800
Indoor air flow (Hi/Med/Lo)		m ³ /h	1790/1537/1348	1718/1218/1029	2691/2310/2021	2777/2351/2005
Indoor air flow (Hi/Med/Lo)		CFM	1052.94/904.12/792.94	1010.59/716.47/605.29	1582.94/1358.82/1188.82	1633.53/1382.94/1179.41
ESP	Rated	Pa	25	37	50	50
	Range	Pa	0-160	0-160	0-160	0-16
Speed (Hi/Med/Lo)		r/min	1050/900/750/650	1050/900/750/650	1000/900/800	1000/900/800
Indoor unit	Body Length(W)	mm	1100	1100	1200	1200
	Body Width(D)	mm	774	774	874	874
	Body Height(H)	mm	249	249	300	300
	Packing Length(W)	mm	1305	1305	1405	1405
	Packing Width(D)	mm	805	805	915	915
	Packing Height(H)	mm	315	315	365	365
	Net/Gross weight (body)	kg	40	41.3	56.8	56.6
RLA (rated current)		A	1.095	1.095	2.75	2.75
Input		W	253.0	253.0	/	/
Fin Spacing		mm	1.4	1.4	1.5	1.5
Fin type (code)			Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
Tube outside	Diameter	mm	Φ7	Φ7	Φ7	Φ7
	Type		Inner groove tube	Inner groove tube	Inner groove tube	Inner groove tube
	Pitch(a)x row pitch(b)	mm	21x13.37	21x13.37	21x13.37	21x13.37
Coil length (height x width)		mm	915x294x40.11	915x294x53.48	1030x378x53.48	1030x378x53.48