



## Multi Zone Inverter Series Cassette

### Serie MM de Inverter Multizona

# MODEL / MODELO: MMCHC\_S

## SPECIFICATIONS / ESPECIFICACIONES

Model			MMCHC09S	MMCHC12S	MMCHC18S	MMCHC24S
Power supply		V-Ph-Hz	208-230~1-60	208-230~1-60	208-230~1-60	208-230~1-60
Indoor air flow (Hi/Med/Lo) (No duct)		m <sup>3</sup> /h	600 / 520 / 460	574 / 490 / 422	956/825/746	1400 / 1250 / 1000
Indoor air flow (Hi/Med/Lo) (No duct)		CFM	353 / 306 / 271	338 / 288 / 248	562/485/439	820 / 740 / 590
Indoor noise level (Hi/Med/Lo) (Standard pressure)		dB(A)	41 / 39 / 37	41 / 38 / 35	46/43/41	51 / 47 / 43
Indoor unit	Dimension (WxDxH) (body)	mm	570 x 570 x 260	570 x 570 x 260	570 x 570 x 260	840 x 840 x 205
	Dimension (WxDxH) (body)	inch	22.44 x 22.44 x 10.24	22.44 x 22.44 x 10.24	22.44 x 22.44 x 10.24	33.07 x 33.07 x 8.07
	Packing (WxDxH) (body)	mm	655 x 655 x 290	655 x 655 x 290	655 x 655 x 290	900 x 900 x 217
	Packing (WxDxH) (body)	inch	25.79 x 25.79 x 11.42	25.79 x 25.79 x 11.42	25.79 x 25.79 x 11.42	35.43 x 35.43 x 8.54
	Dimension (WxDxH) (panel)	mm	647 x 647 x 50	647 x 647 x 50	647 x 647 x 50	950 x 950 x 55
	Dimension (WxDxH) (panel)	inch	25.47 x 25.47 x 1.97	25.47 x 25.47 x 1.97	25.47 x 25.47 x 1.97	37.4 x 37.4 x 2.17
	Packing (WxDxH) (panel)	mm	715 x 715 x 123	715 x 715 x 123	715 x 715 x 123	1035 x 1035 x 90
	Packing (WxDxH) (panel)	inch	28.15 x 28.15 x 4.84	28.15 x 28.15 x 4.84	28.15 x 28.15 x 4.84	40.75 x 40.75 x 3.54
	Net/Gross weight (body)	kg	16 / 19	16 / 19	18 / 21	20.5 / 24
	Net/Gross weight (body)	lbs.	35.27 / 41.88	35.27 / 41.88	39.68 / 46.3	45.19 / 52.91
	Net/Gross weight (panel)	kg	2.5 / 4.5	2.5 / 4.5	2.5 / 4.5	5 / 8
	Net/Gross weight (panel)	lbs.	5.51 / 9.92	5.51 / 9.92	5.51 / 9.92	11.02 / 17.64
Design pressure		PSIG	550 / 340	550 / 340	550 / 340	550 / 340
Drainage water pipe diameter		mm	ODΦ25	ODΦ25	ODΦ25	ODΦ32
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ12.7 (1/4"/1/2")	Φ6.35/Φ12.7 (1/4"/1/2")	Φ9.52/Φ15.9 (3/8"/5/8")
Controller			Remote control	Remote control	Remote control	Remote control
Room temperature	Cooling	°C / °F	17~32 / 62~90	17~32 / 62~90	17~32 / 62~90	17~32 / 62~90
	Heating	°C / °F	0~30 / 32~86	0~30 / 32~86	0~30 / 32~86	0~30 / 32~86
Operation temperature		°C / °F	17~30 / 62~86	17~30 / 62~86	17~30 / 62~86	17~30 / 62~86