



R32 Portable Air Conditioner

R32 aire portatil

MODEL / MODELO: MPNT___AR32

SPECIFICATIONS / ESPECIFICACIONES

Model			MPNT120AR32	MPNT140AR32
Power supply		V,HZ,Ph	115V, 60Hz,1Ph	115V, 60Hz,1Ph
Cooling	Capacity	Btu/h	12000	14000
	Input	W	1355	1555
	Current	A	11.9	11.8
	EER	W/W	2.6	2.64
Btu/W.h		8.9	9.0	
Moisture Removal (26.7/20.9°C)		L/h	1.69	1.83
Moisture Removal (35/28.3°C)		L/h	2.28	2.67
Starting current		A	35	49
Compressor	Model		KSN84E12VBDB1	KSM99E11VEZ
	Type		ROTARY	ROTARY
	Brand		GMCC	GMCC
	Capacity	Btu/h	10628	12096
	Input	W	760	840
	Rated current(RLA)	A	6.7	7.3
	Locked rotor Amp(LRA)	A	35	49
	Thermal protector		N/A	N/A
	Thermal protector position		N/A	N/A
	Capacitor	uF	50	70
Refrigerant oil	ml	190±10	320±15	
Indoor side air flow (Hi)		m3/h	410	430
Indoor side noise level(Hi)		dB(A)	57.5	55
Outdoor side noise level (Hi)		dB(A)	61.5	58
Refrigerant type		ozs	R32/9.52	R32/14.46
Design pressure		Mpa/PSI	3.8/550	3.8/550
Plug type			LCDI	LCDI
Plug Face (NEMA#)			5-15P	5-15P
Power Cord Length (mm.)			1900mm	1800mm
Power Cord Length (ft.)			6.23	5.199
Control type			Remote Control	Remote Control
Operation temp (room temp.)		°C	17-35/---	17-35/---
		°F	62°F~95°F/---	62°F~95°F/---
Dimension (W*D*H)		in.	17.13x13.46x28.35	18.03x14.69x30.51
Packing (W*D*H)		in.	18.70x16.14x34.25	20.08x17.32x34.65
Net/Gross weight		Lb.	57.01/66.58	68.78/79.59