



Dream Inverter Series

Sueño Clasico Inverter



MODEL / MODELO: MWDFDT / MRDFDT

SPECIFICATIONS / ESPECIFICACIONES

Indoor Model		MWDFDT_S		MWDFDT_SA	
Outdoor Model		MRDFDT_AS		MRDFDT_ASA	
Power supply		Ph-V-Hz	220-230V,1Ph,60Hz	115V,1Ph,60Hz	
Cooling	Capacity	Btu/h	11500	11500	
	Input	W	960	960	
	Rated current	A	4.40	8.30	
	SEER	Btu/W	20.5	20.5	
Max. Fuse Indoor		A	15	15	
Max. Fuse Outdoor		A	15	30	
Compressor	Model		KSK103D33UEZ3(YJ)	KSK103D33UEZ3(YJ)	
	Type		Rotary	Rotary	
	Brand		GMCC	GMCC	
	Capacity	W	3250	3250	
	Input	W	834	834	
	Rated current (RLA)	A	5.7	5.7	
	Refrigerant oil / oil charge	ml	ESTER OIL VG74 280 ±15 ml	ESTER OIL VG74 280 ±15 ml	
Indoor unit	Dimension (W*D*H)	inch	31.69*7.59*11.88	31.69*7.59*11.88	
	Packing (W*D*H)	inch	34.44*14.76*11.22	34.44*14.76*11.22	
	Net/Gross weight	lbs	19.62/25.35	19.62/25.13	
Outdoor unit	Dimension (W*D*H)	inch	28.34*19.48*10.62	28.34*19.48*10.62	
	Packing (W*D*H)	inch	32.87*11.81*21.25	32.87*11.81*21.25	
	Net/gross weight	lbs	48.06/52.02	51.14/55.11	
Refrigerant type		lbs	R410A/1.43	R410A/1.43	
Design pressure		MPa	4.2/1.5	4.2/1.5	
Refrigerant piping	Liquid side/ Gas side	inch	1/4 / 3/8	1/4 / 3/8	
	Max. refrigerant pipe length	ft	82	82	
	Max. difference in level	ft	32	32	
Thermostat type			Remote Control	Remote Control	
Room temperature	Indoor (cooling/heating)	°F	62.6~89.6	62.6~89.6	
	Outdoor (cooling/heating)	°F	32~122	32~122	
Application area (Cooling Standard)		m ²	16~23	16~23	