



Golden Fin

# Glacier Inverter Series Serie Galcier Inverter



## MODEL / MODELO: MWGLC\_SA / MRGLC\_ASA SPECIFICATIONS / ESPECIFICACIONES

Indoor Model		MWGLC12SA	
Outdoor Model		MRGLC12ASA	
Power supply		Ph-V-Hz	115V,1Ph,60Hz
Cooling	Capacity (range)	Btu/h	12000(/~/)
	Input	W	1200
	Rated current	A	10.43
	<b>EER</b>	<b>Btu/w</b>	<b>10</b>
	<b>SEER</b>	<b>Btu/w</b>	<b>16.5</b>
Minimum Circuit Ampacity		A	15
Max.Fuse		A	20
Compressor	Model		ASN98D22UFZ
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	2935
	Input	W	748
	Rated current (RLA)	A	/
	Refrigerant oil/oil charge	ml	VG74/370
Indoor air flow (Hi/Mi/Lo)		m3/h	400/350/250
Indoor air flow (Hi/Mi/Lo)		CFM	235.29/205.88/147.06
Indoor noise level (Hi/Mi/Lo)		dB(A)	38.5/0/24.5
Indoor unit	Dimension (W*D*H)	mm	802x189x297
	Packing (W*D*H)	mm	875x285x380
	Net/Gross weight	Kg	8.5/11
Outdoor air flow		m3/h	2000
Outdoor air flow		CFM	1176.47
Outdoor noise level		dB(A)	51.5
Outdoor unit	Dimension (W*D*H)	mm	770x300x555
	Packing (W*D*H)	mm	900x345x595
	Net/Gross weight	Kg	28.3/30.7
Refrigerant type		oz	R410A/20.8
Refrigerant precharge		ft	25
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)
	Max. refrigerant pipe length	m	25
	Max. difference in level	m	10