



Dream Heat Pump Inverter

Sueño Inverter de Bomba de Calor

MODEL / MODELO: MWHDR12SA/MRHR12ASA

SPECIFICATIONS / ESPECIFICACIONES

Model		MWHDR12SA/MRHR12ASA	
Power supply		Ph-V-Hz	115V,1Ph,60Hz
Cooling	Capacity	Btu/h	12000
	Input	W	1260
	Rated Current	A	11.5
	EER	Btu/w	2.79
	SEER		19.8
Heating	Capacity	Btu/h	12000
	Input	W	1200
	Rated Current	A	10.8
	COP	W/W	2.93
Minimum Circuit Ampacity		A	15
Max Fuse		A	15
Indoor Fan Motor	Model		ZKFP-20-8-5
	RLA	W	25.0
	Speed (hi/mi/lo)	r/min	1080/900/700
Indoor air flow (Hi/Med/Lo)		m3/h	520/450/340
Indoor noise level (Hi/Mid/Lo)		dB(A)	41.5/34/26.5
Indoor Unit	Dimension(W*D*H)	mm	805x193x302
	Packing (W*D*H)	mm	875x375x290
	Net/Gross weight	Kg	8.9/11.6
Compressor	Model		ASN98D22UFZ
	Type		ROTARY
	Brand		GMCC
	Capacity	W	2935
	Input	W	748
	Rated current (RLA)	A	5.35
Refrigerant oil		ml	VG74/370
Outdoor fan motor	Model		ZKFN-40-8-1L
	Input	W	63.0
	RLA	A	/
	Speed	r/min	850/650
Outdoor air flow (Max.)		m3/h	2000
Outdoor noise level		dB(A)	53.5
Outdoor Unit	Dimension (WxDxH)	mm	770x300x555
	Packing (WxDxH)	mm	900x345x595
	Net/ Gross weight	Kg	31.3/33.3
Refrigerant piping	Liquid side/ Gas side	mm	6.35mm(1/4in)/12.7mm(1/2in)
Room Temperature	Indoor(cooling/ heating)	°C	17~32/0~30
	Outdoor(cooling/heating)	°C	-15~50/-25~30