

115 V



## R-32 Window Unit

### Unidad de ventana R-32



# MODEL / MODELO: MWRUT

## SPECIFICATIONS / ESPECIFICACIONES

Model		MWRUT06AR	MWRUT08AR	MWRUT10AR	MWRUT12AR	
Power supply	Ph-V-Hz	1Ph-115V-60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz	1Ph-115V-60Hz	
Cooling	RATED Capacity	Btu/h	6000	8000	10000	12000
	RATED EER	W/W (Btu/H/w)	3.25	3.52	3.52	3.52
	RATED Input	W	545	667	835	1000
	RATED Current	A	5.1	5.9	8.03	9.72
Rated input consumption		W	700	865	983.6	1207
Max. current		A	6.5	8.4	9.68	11.99
Starting current		A	20	25.2	29.04	35.97
Compressor	Model	KSN54E11VAJB3	KSN66E11VBZC1	KSN78E11VBZC1	KSM99E11VEZ	
	Type	Rotary	Rotary	Rotary	Rotary	
	Brand	GMCC	GMCC	GMCC	GMCC	
	Capacity	Btu/h	1960	2395	2875	3545
Refrigerant type		ozs	R32	R32	R32	R32
Design pressure		PSI	300/250	300/250	300/520	300/520
Fan motor	Model	YKTS-35-4-60L	YKTS-95-4-52L	YKTS-60-4-56L	YKTS-95-4-52L	
	Capacitor	uF	6	15	15	15
	Speed (H/M/L)	r/min	1540 / 1350 / 1210	1540 / 1340 / 1200	1610 / 1450 / 1310	1610 / 1450 / 1310
Evaporator	Fin spacing	mm	1.2	1.2	1.2	1.2
	Fin type (code)		Hydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium	Hydrophilic aluminium
	Tube outside dia. and type	mm	Φ7, Innergroove tube	Φ7, Innergroove tube	Φ7, Innergroove tube	Φ7, Innergroove tube
	Coil length x height x width	mm	276X210X26.74	320X210X40.11	325X252X40.11	326X252X53.48
	Number of circuits		1	2	2	4
Indoor air flow (Hi/Med/Lo)		m3/h	256/226/199	334/282/254	510/452/408	510/459/408
Indoor noise level (Hi/Med/Lo)		dB(A)	57/55/52	59/57/54	61/58/56	61/59/57
Condenser	Fin spacing	mm	1.2	1.2	1.2	1.2
	Fin type (code)		inner groover tube	inner groover tube	inner groover tube	inner groover tube
	Tube outside dia. and type	mm	Φ5, Innergroove tube	Φ5, Innergroove tube	Φ5, Innergroove tube	Φ5, Innergroove tube
	Coil length x height x width	mm	350 x 290 x 25.12	410 x 319 x 25.12	415 x 351 x 34.8	415 x 348 x 37.68
	Number of circuits		1	2	2	3
Outdoor noise level (H/M/L)		dB(A)	60	65	68.5	66.5
Control type			Remote Control	Remote Control	Remote Control	Remote Control
Operation Temp	Indoor (cooling/heating)	°F	62.6~89.6	62.6~89.6	62.6~89.6	62.6~89.6
	Outdoor (cooling/heating)	°F	64.4~109.4	64.4~109.4	64.4~109.4	64.4~109.4
Application area		m2	8-12	11-16	13-20	16-23
Dimension(W*D*H)		mm	406x335x306	471x400x340	482x545x372	545x482x372
Packing (W*D*H)		mm	455x390x380	560x455x380	586x557x430	545x482x372
Net/Gross weight		kg	17.55/19.85	21.28/24.16	26/29	30.7/34

230 V



## R-32 Window Unit

### Unidad de ventana R-32



# MODEL / MODELO: MWRUT

## SPECIFICATIONS / ESPECIFICACIONES

Model			MWRUT18BR	MWRUT24BR
Power supply		Ph-V-Hz	208/230V,1Ph,60Hz	208/230V,1Ph,60Hz
Cooling	RATED Capacity	Btu/h	18000	24000
	RATED EER	W/W (Btu/H/w)	3.46	3.02
	RATED Input	W	1525/1500	2427/2398
	RATED Current	A	7.2/7.6	12.2/13.0
Rated input consumption		W	2150	3300
Max. current		A	11.5	16.8
Starting current		A	34.5	50.4
Compressor	Model		KSF150N1VETB3	KSG230N1VMT
	Type		Rotary	Rotary
	Brand		GMCC	GMCC
Refrigerant type		ozs	R32	R32
Design pressure		PSI	300/520	300/520
Fan motor	Model		YKSS-140-6-3L	YKSS-150-6-7L
	Capacitor	uF	5	8
	Speed (H/M/L)	r/min	1110/1000/890	1120/1030/930
Evaporator	Fin spacing	mm	1.3	1.2
	Fin type (code)		Hydrophilic aluminium	Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ5, Innergroove tube	Φ5, Innergroove tube
	Coil length x height x width	mm	480x294x53.48	560x315x40.11
	Number of circuits		4	4
Indoor air flow (Hi/Med/Lo)		m3/h	617/557/512	783/752/716
Indoor noise level (Hi/Med/Lo)		dB(A)	57.5/55.5/54.5	59.3/58.5/57.5
Condenser	Fin spacing	mm	1.2	1.2
	Fin type (code)		Unhydrophilic aluminium	Unhydrophilic aluminium
	Tube outside dia. and type	mm	Φ5, Innergroove tube	Φ5, Innergroove tube
	Coil length x height x width	mm	510x390x46.4	585x410x46.4
	Number of circuits		4	4
Outdoor noise level (H/M/L)		dB(A)	66.5/64/61.5	66/65/64
Control type			Remote Control	Remote Control
Operation Temp	Indoor (cooling/heating)	°F	62.6~89.6	62.6~89.6
	Outdoor (cooling/heating)	°F	64.4~109.4	64.4~109.4
Dimension(W*D*H)		mm	600x645x455	673x674x473
Packing (W*D*H)		mm	760x660x495	750x794x520
Net/Gross weight		kg	53.1/60.2	59.1/67.5