



# INSTANT COMFORT SOLUTION



# Features



Sleep Mode



Anti-rust  
Outdoor Casing



Auto Restart



Anti-cold  
Air Function



Hydrophilic  
Aluminium Fin



Turbo



Low Ambient  
Kit



LED Display



Low Noise  
Air Flow System



Inner Grooved  
Cooper Tube



Strong  
Dehumidification



Self  
Diagnosis



Valve Protection  
Cover

## Fixed Speed Mini-Split System

### SPECIFICATIONS / ESPECIFICACIONES

Model		SWECOT12S/SRECOT12DS		SWECOT18S/SRECOT18DS		SWECOT24S/SRECOT24DS	
Power supply		V-Ph-Hz		1Ph / 220V/50Hz		1Ph / 220V/50Hz	
Cooling	Capacity	Btu/h		12000		18000	
	Input	W		1195		1800	
	Rated Current	A		5.60		8.43	
	EER	Btu/w		2.68		2.67	
Max. current		A		7.90		12.44	
Compressor	Model			ASM130V01UDZ		ASF200V01UDTB3	
	Type			Rotary		Rotary	
	Input	W		990		1755	
	Rated current (RLA)	A		4.6		8.2	
Refrigerant				R410A		R410A	
Outdoor noise level		dB(A)		49		52	
Dimensions	Indoor Unit (W×H×D)	mm	inch	800X292X190/ 31.5x11.5x7.5		850X292X190/ 33.5x7.5x11.5	
	Indoor Package (W×H×D)	mm	inch	865X335X240/ 34.1x13.2x9.5		915X335X240/ 36x13.2x9.5	
	Outdoor Unit (W×H×D)	mm	inch	740×302×550/ 29.1x11.9x21.7		800×302×550 / 31.5x11.9x21.7	
	Outdoor Package (W×H×D)	mm	inch	810X355X595 / 31.9x13.97x23.4		870X355X595 / 34.3x13.97x23.4	
Refrigerant piping	Liquid Side	mm	inch	Φ6 / 1/4		Φ6 / 1/4	
	Gas Side	mm	inch	Φ9 / 3/8		Φ12 / 1/2	
	Max. refrigerant pipe length	mm	inch	10 / 0.39		15 / 0.59	
	Max. difference in level	mm	inch	5 / 0.196		10 / 0.39	
Indoor Weight	Net Weight	Kg	lb	7.6 / 16.76		8.5 / 18.7	
	Gross Weight	Kg	lb	8.7 / 19.2		9.7 / 21.4	
Outdoor Weight	Net Weight	Kg	lb	25.5 / 56.2		32.5 / 71.7	
	Gross Weight	Kg	lb	28 / 61.7		35 / 77.2	
Cooling Operation Ambient Temperature Range		°F		60°F-109°F		60°F-109°F	
		°C		16°C-43°C		16°C-43°C	